EPARA HD

16-Channel HD DVR











Features

- Megapixel resolution over standard coaxial / UTP (Unshielded Twisted Pair) cable
- eZ upgrade to HD resolution
- H.264 compression format for enhancing recording capacity
 and improving network image transmission speed
- Multiple Monitors: Separately configured HDMI, VGA ,CVBS
 Monitor outputs
- High bandwidth HD recording (480/400fps) with recordable reduced bandwidth stream for mobile or multiplexed viewing applications
- Supports live monitoring and playback of video from mobile devices via MobileFocus / MobileFocus Plus Apps
- Multiple Control Inputs: mouse / front panel / IR remote controller
- Remote configuration support from built-in web interface
- Gigabit Ethernet interface for remote network viewing and control
- Integration with Genie XMS
- Multi-language support

Dimensions





• All product specifications are subject to change without notice

Models vary in different countries. Please visit EverFocus regional websites for detailed
ordering information

Specifications

EPARA HD Series	EPARA HD 16CH
HD or WD1 Video In	x 16 on BNC
Video Out	HDMI x 1 / VGA x 1 / CVBS x 1
Recording Rate/Resolution	NTSC 480fps@720p; PAL 400fps@720p
Playback Rate/Resolution	NTSC 480fps@720p; PAL 400fps@720p
Compression Format	H.264
Operating System	Linux [®] embedded
Audion In/Out	16 In / 2 Out
Alarm In/Out	16 In / 2 Out
Internal Storage	3.5"HDD x 4 (max 16TB)
External Storage	eSATA x 1
Network/Protocols	10/100 Ethernet x 1/TCP-IP / DHCP / PPPOE / DDNS / SMTP / NTP
USB	USB 2.0 x 2
RS-232/RS-485	0 / 1
Configuration Method	OSD UI / Webpage
Mobile Viewing	iOS, Android
Pentaplex Operation	Simultaneous Live, Recording, Playback, Archive and Remote viewing
Dual Streaming	Yes
Recording Mode	Manual, Schedule, Event
Playback Search	Date/Time search
Video Pause	Yes
Video Loss Detection	Yes
Motion Detection	Yes
Event Log	Yes
Watch dog timer	Yes
Schedule settings	Yes
User Access	2 Levels of user access
PTZ protocols supported	Pelco D, Pelco P, Samsung, Transparent
Power Source	100-240 VAC~
Power Consumption	150W max.
Operating Temp.	0°C~40°C / 32°F~104°F
Dimensions (W x D x H)	430 x 423 x 95 mm / 16.93" x 16.65" x 3.74"
Weight	8.2 kg / 20.83 lbs (without HDDs)
Certificates	CE, FCC,UL